

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name FORCH CAVITY SEALING GOLD L263 / WAX TRANSPARENT PLUS L264 1L
Synonyms CAVITY SEALING GOLD L263 (ART: 6620 6093) • CAVITY WAX TRANSPARENT PLUS L264 (ART: 6620 6095)

1.2 Uses and uses advised against

Uses CAVITY FILLING

1.3 Details of the supplier of the product

Supplier name FORCH AUSTRALIA PTY LTD
Address 2 Forward St, Gnangara, WA, 6077, AUSTRALIA
Telephone (08) 9303 9113
Fax (08) 9303 9114
Email shop@forch.com.au
Website <https://www.forch.com.au/>

1.4 Emergency telephone numbers

Emergency (08) 9303 9113
Emergency 0413 550 330; 0424 135 792

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Flammable Liquids: Category 3

Health Hazards

Aspiration Hazard: Category 1
Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects)
Repeated exposure may cause skin dryness or cracking.

Environmental Hazards

Aquatic Toxicity (Chronic): Category 3

2.2 GHS Label elements

Signal word DANGER

Pictograms



Hazard statements

AUH066 Repeated exposure may cause skin dryness or cracking.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Prevention statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use appropriate media to extinguish.

Storage statements

P403 + P233 + P235	Store in a well-ventilated place. Keep cool. Keep container tightly closed.
P405	Store locked up.

Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content (w/w)
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (<0.1% W/W BENZENE)	64742-48-9	265-150-3	40 to 60%
MINERAL OIL (SOLVENT/HIGHLY REFINED)	-	-	Not Available
ADDITIVE(S)	-	-	Remainder

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Flammable. May evolve carbon oxides and hydrocarbons when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

3Y

3 Normal Foam (protein based foam that is not alcohol resistant).

Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store tightly sealed in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be bunded and have appropriate fire protection and ventilation systems.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Mineral Oil Mist	SWA [AUS]	--	5	--	--
Mineral spirits	SWA [Proposed]	50	295	100	593

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/ explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear nitrile or neoprene gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	Where an inhalation risk exists, wear a Type A (organic vapour) / Organic vapour respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	BROWN LIQUID (AEROSOL DISPENSED)
Odour	MINERAL OIL ODOUR
Flammability	FLAMMABLE
Flash point	40°C (Approximately)
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	0.86
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	240°C (Approximately)
Decomposition temperature	NOT AVAILABLE
Viscosity	40 cSt @ 25°C
Explosive properties	NOT EXPLOSIVE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

9.2 Other information

VOC	480 g/L
------------	---------

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Acute exposure may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (<0.1% W/W BENZENE)	> 5000 mg/kg (OECD TG 401)	> 2000 mg/kg (OECD TG 402)	> 5610 mg/m3 (OECD TG 403)

Skin Contact may result in drying and defatting of the skin, irritation, rash and dermatitis.

Eye Contact may result in irritation, lacrimation, pain and redness.

Sensitisation Not classified as causing skin or respiratory sensitisation.

Mutagenicity Not classified as a mutagen.

Carcinogenicity Not classified as a carcinogen.

Reproductive Not classified as a reproductive toxin.

STOT - single exposure Over exposure may result in irritation of the nose and throat with coughing, as well as central nervous system (CNS) effects including headache, drowsiness and dizziness.

STOT - repeated exposure Not classified as causing organ damage from repeated exposure. However, repeated exposure to some solvents have been reported to cause adverse effects to the central nervous system (CNS).

Aspiration Aspiration into the lungs may result in chemical pneumonitis and pulmonary oedema.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Dispose of by controlled incineration, by licensed or competent personnel. Contact the manufacturer/supplier for additional information (if required). Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1268	1268	1268
14.2 Proper Shipping Name	PETROLEUM PRODUCTS, N.O.S. (contains solvent naphtha petroleum, heavy aliphatic)	PETROLEUM PRODUCTS, N.O.S. (contains solvent naphtha petroleum, heavy aliphatic)	PETROLEUM PRODUCTS, N.O.S. (contains solvent naphtha petroleum, heavy aliphatic)
14.3 Transport hazard class	3	3	3
14.4 Packing Group	III	III	III

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code 3Y
GTEPG 3A1
EmS F-E, S-E

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

Inventory listings **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**
All components are listed on AIIC, or are exempt.
UNITED STATES: TSCA (US Toxic Substances Control Act)
All components are listed on the TSCA inventory, or are exempt.

16. OTHER INFORMATION

Additional information **WORK PRACTICES - SOLVENTS:** Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGES: Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

WORKPLACE CONTROLS AND PRACTICES: Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:
The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmtglobal.com
Web: www.rmtglobal.com

[End of SDS]