



SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name FORCH CONSTRUCTION-SILICONE NEUTRAL MEDIUM VISCOSITY 310ML

Synonyms CONSTRUCTION-SILICONE NEUTRAL MEDIUM VISCOSITY BLACK 310ML (ART: 6810 2104) •

CONSTRUCTION-SILICONE NEUTRAL MEDIUM VISCOSITY TRANSPARENT 310ML (ART: 6810 2100) •

CONSTRUCTION-SILICONE NEUTRAL MEDIUM VISCOSITY WHITE 310ML (ART: 6810 2102)

1.2 Uses and uses advised against

Uses ADHESIVE • ELASTOMER • SEALANT

1.3 Details of the supplier of the product

Supplier name FORCH AUSTRALIA PTY LTD

Address 2 Forward St, Gnangara, WA, 6077, AUSTRALIA

 Telephone
 (08) 9303 9113

 Fax
 (08) 9303 9114

 Email
 shop@forch.com.au

 Website
 https://www.forch.com.au/

1.4 Emergency telephone numbers

Emergency (08) 9303 9113

Emergency 0413 550 330; 0424 135 792

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

2.2 GHS Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
HYDROCARBONS, C15-C19, N-ALKANES, ISOALKANES, <2% AROMATICS	1437281-01-0	940-730-5	1 to <10%
O,O'O"-(METHYLSILYLIDYNE)TRIOXIME 2-PENTANONE	37859-55-5	484-460-1	1 to <5%
2-OCTYL-2H-ISOTHIAZOL-3-ONE	26530-20-1	247-761-7	<0.0015%
CALCIUM CARBONATE	471-34-1	207-439-9	Not Available
METHANOL (EVOLVED)	67-56-1	200-659-6	Not Available
SILICONE(S)	-	-	>60%
SILICA, AMORPHOUS	-	-	Not Available

Ingredient Notes Ingredients (not listed above) are considered trade secret and determined not to be hazardous, below cut off

limits, or do not affect classifications.



SDS Date: 15 Nov 2024 Revision No: 1.1

4. FIRST AID MEASURES

4.1 Description of first aid measures

If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to Eye

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes. Remove contact lenses if present

and easy to do so.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If

swallowed, do not induce vomiting. Rinse mouth with water provided person is conscious.

First aid facilities Normal washroom facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases (carbon/silicon oxides, formaldehyde, methanol) when heated to decomposition.

5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection systems.

7.3 Specific end uses

No information provided.



Revision No: 1.1

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
Ingredient		ppm	mg/m³	ppm	mg/m³
Calcium carbonate (Limestone, Marble, Whiting)	SWA [AUS]		10		
Fumed silica (respirable dust)	SWA [AUS]		2		
Methanol	SWA [AUS]	200	262	250	328

Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
METHANOL (EVOLVED)	ACGIH BEI	Methanol in urine	End of shift	15 mg/L

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction

ventilation is recommended.

PPE

Eye / Face Wear splash-proof goggles.

Hands Wear PVC or rubber gloves. When using large quantities or where heavy contamination is likely, wear

Viton® gloves.

Body When using large quantities or where heavy contamination is likely, wear coveralls.

Respiratory Where an inhalation risk exists, wear a Type A (organic vapour) / Organic vapour respirator.





9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance COLOURED PASTE
Odour CHARACTERISTIC ODOUR

Flammability
NON FLAMMABLE
Flash point
NOT RELEVANT
Boiling point
NOT AVAILABLE
Melting point
NOT AVAILABLE
Evaporation rate
NOT AVAILABLE
NOT AVAILABLE
Vapour density
NOT AVAILABLE

Relative density 0.99

Solubility (water) **INSOLUBLE NOT AVAILABLE** Vapour pressure **NOT AVAILABLE Upper explosion limit** Lower explosion limit NOT AVAILABLE Partition coefficient NOT AVAILABLE **Autoignition temperature** NOT AVAILABLE **Decomposition temperature** NOT AVAILABLE Viscosity NOT AVAILABLE **Explosive properties** NOT EXPLOSIVE **Oxidising properties** NON OXIDISING **Odour threshold NOT AVAILABLE**

10. STABILITY AND REACTIVITY



SDS Date: 15 Nov 2024 Revision No: 1.1

Page 3 of 6

PRODUCT NAME FORCH CONSTRUCTION-SILICONE NEUTRAL MEDIUM VISCOSITY 310ML

10.1 Reactivity

Reacts with water or moisture to form methanol.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerisation is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid exposure to moisture.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon/ silicon oxides, formaldehyde, methanol) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

This product is expected to be of low toxicity. Ingestion is considered unlikely due to product form. **Acute toxicity**

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
2-OCTYL-2H-ISOTHIAZOL-3-ONE	550 mg/kg (rat)	690 mg/kg (rabbit)	
CALCIUM CARBONATE	> 2000 mg/kg (rat)	> 2000 mg/kg (rat)	> 3.0 mg/L
SILICONE(S)	2-49 g/kg (rat)		
SILICA, AMORPHOUS	3160 mg/kg (rat)		

Contact may result in drying and defatting of the skin, rash and dermatitis. Skin

Eve Contact may result in irritation, lacrimation, pain and redness.

Sensitisation Not classified as causing skin or respiratory sensitisation. However, formaldehyde may be evolved during

curing/decomposition which is classified as a skin sensitiser. Contains trace amounts 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction in sensitised individuals. Formaldehyde may be

evolved which is classified as a skin sensitiser.

Mutagenicity Not classified as a mutagen.

Carcinogenicity Not classified as a carcinogen. Formaldehyde may be evolved during curing/decomposition which is

classified as a confirmed human carcinogen (IARC Group 1). Formaldehyde may be evolved which is

classified as a confirmed human carcinogen (IARC Group 1).

Not classified as a reproductive toxin. Reproductive

STOT - single exposure

Over exposure may result in mucous membrane irritation of the respiratory tract, coughing, nausea, dizziness and headache. Acute high level exposure to methanol may lead to visual disturbances, such as

blurred or dimness of vision, leading to blindness.

STOT - repeated

exposure

Not classified as causing organ damage from repeated exposure.

Aspiration Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

SDS Date: 15 Nov 2024 Page 4 of 6 Revision No: 1.1



PRODUCT NAME FORCH CONSTRUCTION-SILICONE NEUTRAL MEDIUM VISCOSITY 310ML

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. For

large quantities, contact the manufacturer/supplier for additional information. Prevent contamination of drains

and waterways as aquatic life may be threatened and environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code None allocated.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the

Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals (GHS Revision 7).

Inventory listings AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)

Some components are listed on AIIC, or are exempt.

16. OTHER INFORMATION

Additional information

SILICONE SEALANTS: Toxic vapours released upon curing may result in eye and respiratory tract irritation. A hazard exists when high concentrations are generated in poorly ventilated areas. Once curing is complete, irritating or toxic vapours should no longer be evolved and therefore an inhalation hazard is no longer anticipated. In this cured state the sealant is considered inert and relatively non toxic.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

Page 5 of 6 SDS Date: 15 Nov 2024
Revision No: 1.1



PRODUCT NAME FORCH CONSTRUCTION-SILICONE NEUTRAL MEDIUM VISCOSITY 310ML

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Email: info@rmtglobal.com Web: www.rmtglobal.com

[End of SDS]



SDS Date: 15 Nov 2024 Revision No: 1.1

Page 6 of 6 Revision