



# **SAFETY DATA SHEET**

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

#### 1.1 Product identifier

Synonyms

## Product name FORCH HIGH-PERFORMANCE-OMC2 SPRAY GREASE S477 500 ML

6500 5610 - ARTICLE NUMBER • HIGH PERFORMANCE GREASE OMC2 • S477

#### 1.2 Uses and uses advised against Uses LUBRICANT

# 1.3 Details of the supplier of the product

Supplier name	FORCH AUSTRALIA PTY LTD
Address	2 Forward St, Gnangara, WA, 6077, AUSTRALIA
Telephone	(08) 9303 9113
Fax	(08) 9303 9114
Email	shop@forch.com.au
Website	https://www.forch.com.au/

#### 1.4 Emergency telephone numbers

Emergency	(08) 9303 9113
Emergency	0413 550 330; 0424 135 792

# 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### **Physical Hazards**

Aerosols - Flammable: Category 1 Aerosols - Pressurised: Category 1 Risk of explosion if heated under confinement.

#### **Health Hazards**

Skin Corrosion/Irritation: Category 2 Serious Eye Damage / Eye Irritation: Category 2A Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects)

## **Environmental Hazards**

Aquatic Toxicity (Acute): Category 3 Aquatic Toxicity (Chronic): Category 2

#### 2.2 GHS Label elements

Signal word DANGER







Hazard statements	
AUH044	Risk of explosion if heated under confinement.
H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H402	Harmful to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
Prevention statements	5
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response statements	
P302 + P352	IF ON SKIN: Wash with plenty of water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment is advised - see first aid instructions.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
Storage statements	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.
Disposal statements	
P501	Dispose of contents/container in accordance with relevant regulations.

#### 2.3 Other hazards

No information provided.

# 3. COMPOSITION/ INFORMATION ON INGREDIENTS

## 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content (w/w)
PETROLEUM GASES, LIQUEFIED (<0.1% W/W 1,3-BUTADIENE)	68476-85-7	270-704-2	26 to 55%
NAPHTHA (PETROLEUM), SOLVENT REFINED LIGHT	64741-84-0	265-086-6	20 to 40%
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (<0.1% W/W BENZENE)	64742-49-0	265-151-9	5 to 15%
ZINC DIALKYLDITHIOPHOSPHATE	4259-15-8	224-235-5	0.1 to 5%

# 4. FIRST AID MEASURES

## 4.1 Description of first aid measures

Еуе	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

# ChemAlert.

**First aid facilities** Eye wash facilities and normal washroom facilities should be available.

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

#### 5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

#### 5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources, including cigarettes, open flames, spark producing switches/tools, heaters, pilot lights, mobile phones, etc when handling. Aerosol cans may explode above 50°C.

#### 5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

#### 5.4 Hazchem code

None allocated.

## 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

#### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

#### 6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

#### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

## 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (< 50°C), dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/ leaking containers. Large storage areas should have appropriate fire protection systems.

## 7.3 Specific end uses

No information provided.



## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1 Control parameters

## Exposure standards

Ingredient	Reference	TWA		STEL	
ingrouoitt	Reference		mg/m³	ppm	mg/m³
Liquefied petroleum gas (LPG)	SWA [AUS]	1000	1800	1000	1800
Mineral Oil Mist	SWA [AUS]		5		

#### **Biological limits**

No biological limit values have been entered for this product.

## 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable vapours may accumulate in poorly ventilated or confined areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

#### PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear nitrile or neoprene gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	At high vapour levels, wear a Type A-Class P1 (organic vapour and particulate) / Organic vapour P100 respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

intormation on basic physical a	na chemical properties
Appearance	GREEN LIQUID (AEROSOL DISPENSED)
Odour	CHARACTERISTIC ODOUR
Flammability	EXTREMELY FLAMMABLE
Flash point	NOT AVAILABLE
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	0.684
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	12 %
Lower explosion limit	1 %
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

# **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.



#### 10.2 Chemical stability

Stable under recommended conditions of storage.

#### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

#### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

#### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

#### 10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

Acute toxicity This product may have the potential to cause adverse health effects if intentionally misused (e.g. deliberately inhaling contents).

## Information available for the ingredients:

Ingredient		Oral LD50	Dermal LD50	Inhalation LC50
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (<0.1% W/W BENZENE)		> 5000 mg/kg (OECD TG 401)	> 2000 mg/kg (OECD TG 402)	> 5610 mg/m3 (OECD TG 403)
Skin	Contact may result in drying and defatting of the skin, irritation, rash and derma			
Eye	Contact may result in irritati	Contact may result in irritation, lacrimation, pain and redness.		
Sensitisation	Not classified as causing sk	Not classified as causing skin or respiratory sensitisation.		
Mutagenicity	Not classified as a mutagen	Not classified as a mutagen.		
Carcinogenicity	Not classified as a carcinog	Not classified as a carcinogen.		
Reproductive	Not classified as a reproductive toxin.			
STOT - single exposure	Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposur may result in nausea, dizziness and drowsiness.			
STOT - repeated exposure	Not classified as causing organ damage from repeated exposure.			
Aspiration	Ingestion is considered unlikely due to product form. However, if liquid component is ingested, aspiration the lungs may cause chemical pneumonitis and pulmonary oedema.		is ingested, aspiration into	

## 12. ECOLOGICAL INFORMATION

#### 12.1 Toxicity

Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

No information provided.

## 12.3 Bioaccumulative potential

No information provided.

# 12.4 Mobility in soil

No information provided.

## 12.5 Other adverse effects

Avoid contamination of drains and waterways.

# 13. DISPOSAL CONSIDERATIONS



#### 13.1 Waste treatment methods

**Waste disposal** For small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. Do not puncture or incinerate aerosol cans. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

#### CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1950	1950	1950
14.2 Proper Shipping Name	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport hazard class	2.1	2.1	2.1
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Marine Pollutant.

#### 14.6 Special precautions for user

Hazchem code	None allocated.
GTEPG	2D1
EmS	F-D, S-U
Other information	The environmentally hazardous substance mark is not required when transported in packages of less than 5 kg/L (UN Model Regulations: Special Provision 375; IATA: Special Provision A197; IMDG: Special Provision 969) or less than 500 kg/L by Australian Road and Rail.

# **15. REGULATORY INFORMATION**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- **Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
- **Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

#### Inventory listings AUSTRALIA: AllC (Australian Inventory of Industrial Chemicals) All components are listed on AlIC, or are exempt.

## **16. OTHER INFORMATION**

Additional information AEROSOL CANS may explode at temperatures approaching 50°C.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.



PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

#### HEALTH EFFECTS FROM EXPOSURE:

ACGIH

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

American Conference of Governmental Industrial Hygienists

#### Abbreviations

	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
	GHS	Globally Harmonized System
	GTEPG	Group Text Emergency Procedure Guide
	IARC	International Agency for Research on Cancer
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m³	Milligrams per Cubic Metre
	OEL	Occupational Exposure Limit
	рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	SWA	Safe Work Australia
	TLV	Threshold Limit Value
	TWA	Time Weighted Average
Report status		ent has been compiled by RMT on behalf of the manufacturer, importer or supplier of the serves as their Safety Data Sheet ('SDS').
	manufacture the current at the time	on information concerning the product which has been provided to RMT by the er, importer or supplier or obtained from third party sources and is believed to represent state of knowledge as to the appropriate safety and handling precautions for the product of issue. Further clarification regarding any aspect of the product should be obtained of the manufacturer, importer or supplier.
	not provide no liability f	has taken all due care to include accurate and up-to-date information in this SDS, it does any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts or any loss, injury or damage (including consequential loss) which may be suffered or any person as a consequence of their reliance on the information contained in this SDS.
Prepared by	5 Ventnor Å Western Au Phone: +61 Fax: +61 8 9	8 9322 1711

# [End of SDS]

Web: www.rmtglobal.com