



SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name FORCH GASKET COMPOUND FOR ENGINES AND HOUSINGS FOR "THE RED" K163 50 G

Synonyms 6480 4525 - ARTICLE NUMBER ● GASKET COMPOUND FOR ENGINES AND HOUSINGS FOR "THE RED"

Page 1 of 7

K163

1.2 Uses and uses advised against

Uses GASKET ADHESIVE ◆ SEALANT

1.3 Details of the supplier of the product

Supplier name FORCH AUSTRALIA PTY LTD

Address 2 Forward St, Gnangara, WA, 6077, AUSTRALIA

 Telephone
 (08) 9303 9113

 Fax
 (08) 9303 9114

 Email
 shop@forch.com.au

Website https://www.forch.com.au/

1.4 Emergency telephone numbers

Emergency (08) 9303 9113

Emergency 0413 550 330; 0424 135 792

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Not classified as a Physical Hazard

Health Hazards

Skin Sensitisation: Category 1

Serious Eye Damage / Eye Irritation: Category 2A

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word WARNING

Pictograms



Hazard statements

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.



SDS Date: 02 Oct 2024

PRODUCT NAME FORCH GASKET COMPOUND FOR ENGINES AND HOUSINGS FOR "THE RED" K163 50 G

Prevention statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Specific treatment is advised - see first aid instructions. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P337 + P313 If eye irritation persists: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage statements

None allocated.

Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	109-16-0	203-652-6	25 to 75%
HYDROXYPROPYL METHACRYLATE	27813-02-1	248-666-3	<15%
CUMENE HYDROPEROXIDE	80-15-9	201-254-7	0.1 to 1%

4. FIRST AID MEASURES

4.1 Description of first aid measures

If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to Eve

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or

an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Page 2 of 7

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If Ingestion

swallowed, do not induce vomiting.

First aid facilities Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Combustible. May evolve carbon oxides and hydrocarbons when heated to decomposition.



SDS Date: 02 Oct 2024

PRODUCT NAME FORCH GASKET COMPOUND FOR ENGINES AND HOUSINGS FOR "THE RED" K163 50 G

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Only trained personnel should undertake clean up.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation and fire protection systems.

Page 3 of 7

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

No exposure standards have been entered for this product.

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.



SDS Date: 02 Oct 2024

PRODUCT NAME FORCH GASKET COMPOUND FOR ENGINES AND HOUSINGS FOR "THE RED" K163 50 G

PPE

Eye / Face Wear splash-proof goggles. **Hands** Wear butyl or nitrile gloves.

Body Wear coveralls.

Respiratory Where an inhalation risk exists, wear a Type A (organic vapour) / Organic vapour respirator.







9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance RED PASTE

Odour CHARACTERISTIC ODOUR Flammability CLASS C2 COMBUSTIBLE

Flash point 95°C Boiling point 261°C

Melting pointNOT AVAILABLEEvaporation rateNOT AVAILABLEpHNOT AVAILABLEVapour densityNOT AVAILABLE

Relative density 1.0 to 1.1

Solubility (water)
Vapour pressure
Upper explosion limit
Lower explosion limit
Partition coefficient

SLIGHTLY SOLUBLE
NOT AVAILABLE
NOT AVAILABLE
NOT AVAILABLE

Autoignition temperature > 400°C

Decomposition temperatureNOT AVAILABLEViscosityNOT AVAILABLEExplosive propertiesNOT EXPLOSIVEOxidising propertiesNOT AVAILABLEOdour thresholdNOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

May polymerise with violent rupture/explosion.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

May polymerise in contact with oxidising agents (e.g. nitrates), acids (e.g. nitric acid), amines, UV light, alkalis (e.g. sodium hydroxide), or if heated. Polymerisation may generate heat with potential for fire-explosion.

Page 4 of 7

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

11. TOXICOLOGICAL INFORMATION



SDS Date: 02 Oct 2024

PRODUCT NAME FORCH GASKET COMPOUND FOR ENGINES AND HOUSINGS FOR "THE RED" K163 50 G

11.1 Information on toxicological effects

Acute toxicity Acute exposure may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	10750 mg/kg (mouse)		
CUMENE HYDROPEROXIDE	382 mg/kg (rat)	500 mg/kg (rat)	1.37 mg/L/4hrs (rat)

Skin Contact may result in irritation, rash and dermatitis.

Contact may result in irritation, lacrimation, pain, redness and possible serious eye damage. Eve Sensitisation May cause an allergic skin reaction. This product is not classified as a respiratory sensitiser.

Mutagenicity Not classified as a mutagen. Carcinogenicity Not classified as a carcinogen. Reproductive Not classified as a reproductive toxin.

Over exposure may result in irritation of the nose and throat, coughing, nausea and headache. High level STOT - single exposure may result in dizziness, drowsiness, breathing difficulties and unconsciousness. exposure

STOT - repeated

exposure

Not classified as causing organ damage from repeated exposure.

Aspiration Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Waste disposal

Page 5 of 7

Contact the manufacturer/supplier for additional information if disposing of large quantities (if required). Prevent contamination of drains and waterways as aquatic life may be threatened and environmental

damage may result.

Dispose of in accordance with relevant local legislation. Legislation

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA



SDS Date: 02 Oct 2024

PRODUCT NAME FORCH GASKET COMPOUND FOR ENGINES AND HOUSINGS FOR "THE RED" K163 50 G

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code None allocated.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the

Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals (GHS Revision 7).

Inventory listings AUSTRALIA: AllC (Australian Inventory of Industrial Chemicals)

All components are listed on AIIC, or are exempt.

EUROPE: EINECS (European Inventory of Existing Chemical Substances)

All components are listed on EINECS, or are exempt.

16. OTHER INFORMATION

Additional information

WORKPLACE CONTROLS AND PRACTICES: Unless a less toxic chemical can be substituted for a hazardous substance, ENGINEERING CONTROLS are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

Page 6 of 7

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



SDS Date: 02 Oct 2024

PRODUCT NAME FORCH GASKET COMPOUND FOR ENGINES AND HOUSINGS FOR "THE RED" K163 50 G

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Email: info@rmtglobal.com Web: www.rmtglobal.com

[End of SDS]



SDS Date: 02 Oct 2024