

Theo Forch Polinox 400 MI Forch Australia Pty Ltd

Chemwatch: 23-5897 Version No: 4.1.1.1 Safety Data Sheet according to WHS and ADG requirements Chemwatch Hazard Alert Code: 4

Issue Date: 01/11/2019 Print Date: 22/02/2021 S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Theo Forch Polinox 400 MI
Chemical Name	Not Applicable
Synonyms	Art.: 6130 1797; 6134 1797; Art.: 6130 1797, 6134 1797
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Polishing liquid.
	Use according to manufacturer's directions.

Details of the supplier of the safety data sheet

Registered company name	Forch Australia Pty Ltd		
Address	2 Forward Street Gnagnara WA 6077 Australia		
Telephone	+61 8 9303 9113		
Fax	+61 8 9303 9114		
Website	www.forch.com.au		
Email	admin@forch.com.au		

Emergency telephone number

Association / Organisation	+61 8 9303 9113	
Emergency telephone numbers	0413 550 330 (Terry Childs)	
Other emergency telephone numbers	0424 135 792	

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

ChemWatch Hazard Ratings

Page 2 of 13

Theo Forch Polinox 400 MI

	Min	Max	
Flammability	4		
Toxicity	1 📃		
Body Contact	2		0 = Minimum
Reactivity	1		2 = Moderate
Chronic	0	1	3 = High 4 = Extreme

Poisons Schedule Not Applica	ble
Classification ^[1] Flammable (narcotic ef	Aerosols Category 1, Skin Corrosion/Irritation Category 2, Specific target organ toxicity - single exposure Category 3 fects), Aspiration Hazard Category 1, Acute Aquatic Hazard Category 2
Legend: 1. Classifie Annex VI	d by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 -

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H222	Extremely flammable aerosol.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H304	May be fatal if swallowed and enters airways.	
H401	Toxic to aquatic life.	
AUH044	Risk of explosion if heated under confinement.	

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.	
P261	Avoid breathing mist/vapours/spray.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/	

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/		
P331	Do NOT induce vomiting.		
P312	Call a POISON CENTER/doctor/ if you feel unwell.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P332+P313	If skin irritation occurs: Get medical advice/attention.		
P362+P364	Take off contaminated clothing and wash it before reuse.		

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
93763-35-0	0.1-<10	hydrocarbons, C9-16, hydrotreated, dearomatised
68439-46-3	1-<3	alcohols C9-11 ethoxylated
8008-20-6	1-<10	kerosene
68476-85-7.	21-50	hydrocarbon propellant

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If aerosols come in contact with the eyes: Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.
Inhalation	 If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 Avoid giving milk or oils. Avoid giving alcohol. Not considered a normal route of entry.

Indication of any immediate medical attention and special treatment needed

For petroleum distillates

- In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
- Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.
- · Positive pressure ventilation may be necessary.
- · Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.
- After the initial episode, individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.
- Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications.
 Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur.Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

BP America Product Safety & Toxicology Department Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

SMALL FIRE: • Water spray, dry chemical or CO2 LARGE FIRE:

Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot.
Fire/Explosion Hazard	 Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition with violent container rupture. Aerosol cans may explode on exposure to naked flames. Combustion products include: carbon dioxide (CO2) nitrogen oxides (NOx) other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. Wipe up. If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

	Avoid all personal contact, including inhalation.
	Wear protective clothing when risk of exposure occurs.
	Use in a well-ventilated area.
Safe handling	Prevent concentration in hollows and sumps.
	DO NOT enter confined spaces until atmosphere has been checked.
	Avoid smoking, naked lights or ignition sources.
	Avoid contact with incompatible materials.

	 Store below 38 deg. C. Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can
	Store in original containers in approved flammable liquid storage area.
Other information	DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
	No smoking, naked lights, heat or ignition sources.
	Keep containers securely sealed. Contents under pressure.
	Store away from incompatible materials.
	Store in a cool, dry, well ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	 Aerosol dispenser. Check that containers are clearly labelled.
Storage incompatibility	Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	kerosene	Oil mist, refined mineral	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	hydrocarbon propellant	LPG (liquified petroleum gas)	1000 ppm / 1800 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	Material name		TEEL-1	TEEL-2	TEEL-3
kerosene	Jet fuels, (JP-5 and JP-8); (Kerosene, 8008-20-6, Fuel Oil No. 1)		Not Available	Not Available	4,800 mg/m3
hydrocarbon propellant	Liquified petroleum gas; (L.P.G.)		65,000 ppm	2.30E+05 ppm	4.00E+05 ppm
Ingredient	Original IDLH Revise		vised IDLH		
hydrocarbons, C9-16, hydrotreated, dearomatised	Not Available	Not Available			
alcohols C9-11 ethoxylated	Not Available	Not Available			
kerosene	2,500 mg/m3	Not Available			

Not Available

Occupational Exposure Banding

2,000 ppm

hydrocarbon propellant

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
hydrocarbons, C9-16, hydrotreated, dearomatised	E	≤ 0.1 ppm	
alcohols C9-11 ethoxylated	E	≤ 0.1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

Page 6 of 13

Theo Forch Polinox 400 MI

Personal protection	
Eye and face protection	No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE: For potentially moderate or heavy exposures: • Safety glasses with side shields. • NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.
Skin protection	See Hand protection below
Hands/feet protection	 No special equipment needed when handling small quantities. OTHERWISE: For potentially moderate exposures: Wear general protective gloves, eg. light weight rubber gloves. For potentially heavy exposures: Wear chemical protective gloves, eg. PVC. and safety footwear.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: • Overalls. • Skin cleansing cream. • Eyewash unit. • Do not spray on hot surfaces.

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator Full-Face Respirator		Powered Air Respirator		
up to 10 x ES	AX-AUS P2	-	AX-PAPR-AUS / Class 1 P2		
up to 50 x ES	-	AX-AUS / Class 1 P2	-		
up to 100 x ES	-	AX-2 P2	AX-PAPR-2 P2 ^		

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Brown highly flammable liquid with perfumed odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	1.14
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	>100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available

Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	1.8 @20C	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. WARNING:Intentional misuse by concentrating/inhaling contents may be lethal .
	exposure to hydrocarbons may result in irregularity of neart beat. Symptoms of moderate poisoning may include dizziness, headache, nausea.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Spray mist may produce discomfort Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons. Not considered to be a risk because of the extreme volatility of the gas.
Chronic	There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population. Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.

Theo Forch Polinox 400 M

Theo Forch Polinox 400 MI	TOXICITY	IRRITATION
	Not Available	Not Available
hvdrocarbons, C9-16.	ΤΟΧΙCITY	IRRITATION
hydrotreated,	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
dearomatised	Oral(Rat) LD50; >5000 mg/kg ^[1]	Skin: adverse effect observed (irritating) ^[1]
	ΤΟΧΙCITY	IRRITATION
	Dermal (rabbit) LD50: >0.002 mg/kg ^[2]	Eye (human): SEVERE
cohols C9-11 ethoxylated	Oral(Rat) LD50; >5050 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]
		Skin: SEVERE
	ΤΟΧΙCITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
kerosene	Inhalation(Rat) LC50; >5.28 mg/l4hrs ^[2]	Skin (rabbit): 500 mg SEVERE
	Oral(Rat) LD50; >5000 mg/kg ^[2]	Skin: adverse effect observed (irritating) ^[1]
	ΤΟΧΙCITY	IRRITATION
hydrocarbon propellant	Inhalation(Rat) LC50; 658 mg/l4hrs ^[2]	Not Available
Legend:	1. Value obtained from Europe ECHA Registered Sub Unless otherwise specified data extracted from RTEC	ostances - Acute toxicity 2.* Value obtained from manufacturer's SDS. CS - Register of Toxic Effect of chemical Substances

ALCOHOLS C9-11 ETHOXYLATED	Somnolence, ataxia, diarrhoea recorded. Polyethers (such as ethoxylated surfactants and polyethylene glycols) are highly susceptible to being oxidized in the air. They then form complex mixtures of oxidation products. Animal testing reveals that whole the pure, non-oxidised surfactant is non-sensitizing, many of the oxidation products are sensitisers. The oxidization products also cause irritation. Humans have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents and other cleaning products. Exposure to these chemicals can occur through swallowing, inhalation, or contact with the skin or eyes. Studies of acute toxicity show that relatively high volumes would have to occur to produce any toxic response. No death due to poisoning with alcohol ethoxylates has ever been reported. Studies show that alcohol ethoxylates have low toxicity through swallowing and skin contact. Animal studies show these chemicals may produce gastrointestinal irritation, stomach ulcers, hair standing up, diarrhea and lethargy. Slight to severe irritation occurred when undiluted alcohol ethoxylates were applied to the skin and eyes of animals. These chemicals show no indication of genetic toxicity or potential to cause mutations and cancers. Both laboratory and animal testing has shown that there is no evidence for alcohol ethoxylates (AEs) causing genetic damage, mutations or cancer. No adverse reproductive or developmental effects were observed. Tri-ethylene glycol ethers undergo enzymatic oxidation to toxic alkoxy acids. They may irritate the skin and the eyes. At high oral doses, they may cause depressed reflexes, flaccid muscle tone, breathing difficulty and coma. Death may result in experimental animal. However, repeated exposure may cause dose dependent damage to the kidneys as well as reproductive and developmental defects. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irri
KEROSENE	Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins. The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell. The gut cell may play a major role in determining the proportion of hydrocarbon that becomes available to be deposited unchanged in peripheral tissues such as in the body fat stores or the liver.
HYDROCARBON PROPELLANT	inhalation of the gas
HYDROCARBONS, C9-16, HYDROTREATED, DEAROMATISED & KEROSENE	For petroleum: This product contains benzene, which can cause acute myeloid leukaemia, and n-hexane, which can be metabolized to compounds which are toxic to the nervous system. This product contains toluene, and animal studies suggest high concentrations of toluene lead to hearing loss. This product contains ethyl benzene and naphthalene, from which animal testing shows evidence of tumour formation. Cancer-causing potential: Animal testing shows inhaling petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans.

	Mutation-causing potential: Most studies involving gasoline have returned negative results regarding the potential to cause mutations, including all recent studies in living human subjects (such as in petrol service station attendants). Reproductive toxicity: Animal studies show that high concentrations of toluene (>0.1%) can cause developmental effects such as lower birth weight and developmental toxicity to the nervous system of the foetus. Other studies show no adverse effects on the foetus. Human effects: Prolonged or repeated contact may cause defatting of the skin which can lead to skin inflammation and may make the skin more susceptible to irritation and penetration by other materials. Animal testing shows that exposure to gasoline over a lifetime can cause kidney cancer, but the relevance in humans is questionable. Kerosene may produce varying ranges of skin irritation, and a reversible eye irritation (if eyes are washed). Skin may be cracked or flaky and/or leathery, with crusts and/or hair loss. It may worsen skin cancers. There may also be loss of weight, discharge from the nose, excessive tiredness, and wheezing. The individual may be pale. There may be increase in the weight of body organs. There was no evidence of harm to pregnancy.		
HYDROCARBONS, C9-16, HYDROTREATED, DEAROMATISED & HYDROCARBON PROPELLANT	No significant acute toxicological data identified in literature search.		
ALCOHOLS C9-11 ETHOXYLATED & KEROSENE	The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.		
A		0	
Acute loxicity	×	Carcinogenicity	*
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	*
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
	Le	gend: 🗙 – Data either not ava	ilable or does not fill the criteria for classification

Legend:

Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)		Species		Value	Source
Theo Forch Polinox 400 MI	Not Available	Not Available		Not Available		Not Available	Not Available
	Endpoint	Test Duration (hr)		Species		Value	Source
hydrocarbons C9-16	LC50	96		Fish		18mg/L	2
hydrotreated,	EC50	48		Crustacea		1.4mg/L	2
dearomatised	EC50	72		Algae or other aquatic plants		3.7mg/L	2
	NOEL	96		Algae or other aquatic plants		0.2mg/L	2
alcohols C9-11 ethoxylated	Endpoint	Test Duration (hr)	Sp	ecies	Value)	Source
	LC50	96	Fis	h	-6-12	mg/L	4
	EC50	48	Cru	ustacea	-2.21	7-3.523mg/L	4
	EC50	96	Alg	ae or other aquatic plants	1.4mg	g/L	2
	NOEC	240	Fis	h	0.16n	ng/L	2
	Endpoint	Test Duration (hr)		Species		Value	Source
	LC50	96		Fish		18mg/L	2
kerosene	EC50	48 Crus		Crustacea		1.4mg/L	2
	EC50	72		Algae or other aquatic plants		3.7mg/L	2
	NOEL	72		Algae or other aquatic plants		0.2mg/L	2
hydrocarbon propellant	Endpoint	Test Duration (hr)		Species		Value	Source
	LC50	96		Fish		24.11mg/L	2
	EC50	96		Algae or other aquatic plants		7.71mg/L	2

	LC50	96	Fish	24.11mg/L	2
	EC50	96	Algae or other aquatic plants	7.71mg/L	2
Legend:	Extracted froi 3. EPIWIN Su ECETOC Aqu Vendor Data	n 1. IUCLID Toxicity Data 2. Europe ECHA R iite V3.12 (QSAR) - Aquatic Toxicity Data (Es iatic Hazard Assessment Data 6. NITE (Japa	egistered Substances - Ecotoxicological Info timated) 4. US EPA, Ecotox database - Aqua n) - Bioconcentration Data 7. METI (Japan) -	mation - Aqua tic Toxicity Dat Bioconcentrati	tic Toxicity ta 5. ion Data 8.

Toxic to aquatic organisms.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility	
	No Data available for all ingredients	

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging disposal	 DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans. Bury residues and emptied aerosol cans at an approved site.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO	
HAZCHEM	Not Applicable	

Land transport (ADG)

UN number	1950	1950		
UN proper shipping name	AEROSOLS	AEROSOLS		
Transport hazard class(es)	Class 2.1 Subrisk Not	pplicable		
Packing group	Not Applicable			
Environmental hazard	Not Applicable	Not Applicable		
Special precautions for user	Special provisio	s 63 190 277 327 344 381 1000ml		

Air transport (ICAO-IATA / DGR)

UN number	1950			
UN proper shipping name	Aerosols, flammable	Aerosols, flammable		
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk	2.1 Not Applicable		
	ERG Code	10L		
Packing group	Not Applicable	Not Applicable		
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions		A145 A167 A802	
	Cargo Only Packing Instructions		203	-
	Cargo Only Maximum Qty / Pack		150 kg	-
	Passenger and Cargo Packing Instructions		203	-
	Passenger and Cargo Maximum Qty / Pack		75 kg	-
	Passenger and Cargo Limited Quantity Packing Instructions		Y203	-
	Passenger and Cargo Limited Maximum Qty / Pack		30 kg G	-

Sea transport (IMDG-Code / GGVSee)

UN number	1950			
UN proper shipping name	AEROSOLS			
Transport hazard class(es)	IMDG Class2.1IMDG SubriskNot Applicable			
Packing group	Not Applicable			
Environmental hazard	Not Applicable	Not Applicable		
Special precautions for user	EMS Number Special provisions Limited Quantities	F-D , S-U 63 190 277 327 344 381 959 1000 ml		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
hydrocarbons, C9-16, hydrotreated, dearomatised	Not Available
alcohols C9-11 ethoxylated	Not Available
kerosene	Not Available
hydrocarbon propellant	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
hydrocarbons, C9-16, hydrotreated, dearomatised	Not Available
alcohols C9-11 ethoxylated	Not Available
kerosene	Not Available
hydrocarbon propellant	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

hydrocarbons, C9-16, hydrotreated, dearomatised is found on the following regulatory lists

Page **12** of **13**

Theo Forch Polinox 400 MI

Australia Hazardous Chemica	al Information System	(HCIS) - Hazardous Chemicals
-----------------------------	-----------------------	------------------------------

alcohols C9-11 ethoxylated is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

kerosene is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

hydrocarbon propellant is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

National Inventory Status

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	No (hydrocarbons, C9-16, hydrotreated, dearomatised)		
Canada - DSL	No (hydrocarbons, C9-16, hydrotreated, dearomatised)		
Canada - NDSL	No (hydrocarbons, C9-16, hydrotreated, dearomatised; alcohols C9-11 ethoxylated; kerosene; hydrocarbon propellant)		
China - IECSC	No (hydrocarbons, C9-16, hydrotreated, dearomatised)		
Europe - EINEC / ELINCS / NLP	No (alcohols C9-11 ethoxylated)		
Japan - ENCS	No (hydrocarbons, C9-16, hydrotreated, dearomatised; alcohols C9-11 ethoxylated)		
Korea - KECI	Yes		
New Zealand - NZIoC	No (hydrocarbons, C9-16, hydrotreated, dearomatised)		
Philippines - PICCS	No (hydrocarbons, C9-16, hydrotreated, dearomatised)		
USA - TSCA	No (hydrocarbons, C9-16, hydrotreated, dearomatised)		
Taiwan - TCSI	No (hydrocarbons, C9-16, hydrotreated, dearomatised)		
Mexico - INSQ	No (hydrocarbons, C9-16, hydrotreated, dearomatised)		
Vietnam - NCI	No (hydrocarbons, C9-16, hydrotreated, dearomatised)		
Russia - ARIPS	No (alcohols C9-11 ethoxylated)		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)		

SECTION 16 Other information

Revision Date	01/11/2019
Initial Date	05/05/2010

SDS Version Summary

Version	lssue Date	Sections Updated
3.1.1.1	11/07/2018	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Advice to Doctor, Appearance, Chronic Health, Classification, Disposal, Environmental, Exposure Standard, Fire Fighter (fire/explosion hazard), Fire Fighter (fire fighting), First Aid (eye), First Aid (swallowed), Ingredients, Personal Protection (other), Personal Protection (Respirator), Physical Properties, Spills (major), Storage (storage incompatibility), Storage (storage requirement), Supplier Information, Use
4.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.