



SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name FORCH RTV SILICONE MOTOR / HOUSING SEALING COMPOUND 200 ML

Synonyms BLACK (ART: 6480 4563) ● GREY (ART: 6480 4564)

1.2 Uses and uses advised against

Uses SEALANT ● SILICONE SEALANT

1.3 Details of the supplier of the product

Supplier name FORCH AUSTRALIA PTY LTD

Address 2 Forward St, Gnangara, WA, 6077, AUSTRALIA

 Telephone
 (08) 9303 9113

 Fax
 (08) 9303 9114

 Email
 shop@forch.com.au

 Website
 https://www.forch.com.au/

1.4 Emergency telephone numbers

Emergency (08) 9303 9113

Emergency 0413 550 330; 0424 135 792

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Aerosols - Flammable: Category 1 Aerosols - Pressurised: Category 1

Health Hazards

Not classified as a Health Hazard

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

Prevention statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

ChemAlert.

PRODUCT NAME FORCH RTV SILICONE MOTOR / HOUSING SEALING COMPOUND 200 ML

Response statements

None allocated.

Storage statements

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Disposal statements

None allocated.

2.3 Other hazards

No information provided.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
O,O'O"-(METHYLSILYLIDYNE)TRIOXIME 2-PENTANONE	37859-55-5	484-460-1	1 to <5%
ADDITIVE(S)	-	-	Remainder
FERRITE	68186-94-7	269-056-3	10 to 20%

Ingredient Notes

Ingredients (not listed above) are considered trade secret and determined not to be hazardous, below cut off limits, or do not affect classifications.

4. FIRST AID MEASURES

4.1 Description of first aid measures

If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to Eye

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or Inhalation

an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If Ingestion

swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

First aid facilities Eye wash facilities and a hand wash basin are recommended.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways. Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. May evolve toxic gases (carbon oxides, silicon oxides, nitrogen oxides, formaldehyde, hydrogen cyanide, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources, including cigarettes, open flames, spark producing switches/tools, heaters, pilot lights, mobile phones, etc when handling. Aerosol cans may explode above 50°C.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

None allocated.

ChemAlert. Page 2 of 7 Revision No: 1.2

SDS Date: 03 Oct 2024

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (< 50°C), dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/ leaking containers. Large storage areas should have appropriate fire protection systems.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

No exposure standards have been entered for this product.

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof **Engineering controls**

extraction ventilation is recommended. Flammable vapours may accumulate in poorly ventilated or confined areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

PPE

Eye / Face Wear splash-proof goggles. Wear PVC or rubber gloves. Hands

When using large quantities or where heavy contamination is likely, wear coveralls. **Body**

At high vapour levels, wear a Type A-Class P1 (organic vapour and particulate) / Organic vapour P100 Respiratory

respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

COLOURED LIQUID (AEROSOL DISPENSED) **Appearance** CHARACTERISTIC ODOUR Odour

ChemAlert.

PRODUCT NAME FORCH RTV SILICONE MOTOR / HOUSING SEALING COMPOUND 200 ML

9.1 Information on basic physical and chemical properties

Flammability EXTREMELY FLAMMABLE

Flash point < 23°C

Boiling pointNOT AVAILABLEMelting pointNOT AVAILABLEEvaporation rateNOT AVAILABLEpHNOT AVAILABLE

Vapour density NOT AVAILABLE

Relative density 1 16 **INSOLUBLE** Solubility (water) NOT AVAILABLE Vapour pressure **NOT AVAILABLE** Upper explosion limit **NOT AVAILABLE** Lower explosion limit **NOT AVAILABLE** Partition coefficient Autoignition temperature NOT AVAILABLE **Decomposition temperature** NOT AVAILABLE **Viscosity** NOT AVAILABLE **Explosive properties** NOT AVAILABLE Oxidising properties NOT AVAILABLE

NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Odour threshold

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, silicon oxides, nitrogen oxides, formaldehyde, hydrogen cyanide, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met. This product may have the potential to cause

adverse health effects if intentionally misused (e.g. deliberately inhaling contents).

Skin Not classified as an irritant. Contact may result in mild irritation, drying and defatting of the skin, rash and

dermatitis

Eye Not classified as an eye irritant. Contact may cause discomfort, lacrimation and redness.

Sensitisation Not classified as causing skin or respiratory sensitisation.

 Mutagenicity
 Not classified as a mutagen.

 Carcinogenicity
 Not classified as a carcinogen.

 Reproductive
 Not classified as a reproductive toxin.

STOT - single

Not classified as causing organ damage from single exposure. However, over exposure may result in mild irritation of the nose and throat, with coughing. High level exposure may result in dizziness, nausea and

headache.

STOT - repeated

exposure

Not classified as causing organ damage from repeated exposure.

Aspiration Ingestion is considered unlikely due to product form.



12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

Contains non readily biodegradable component(s).

12.3 Bioaccumulative potential

Not expected to bioaccumulate.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. Do not

puncture or incinerate aerosol cans. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1950	1950	1950
14.2 Proper Shipping Name	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport hazard class	2.1	2.1	2.1
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code None allocated.

GTEPG 2D1 **EmS** F-D, S-U

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the

Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals (GHS Revision 7).



PRODUCT NAME FORCH RTV SILICONE MOTOR / HOUSING SEALING COMPOUND 200 ML

Inventory listings AUSTRALIA: AllC (Australian Inventory of Industrial Chemicals)

All components are listed on AIIC, or are exempt.

UNITED STATES: TSCA (US Toxic Substances Control Act)All components are listed on the TSCA inventory, or are exempt.

16. OTHER INFORMATION

Additional information

AEROSOL CANS may explode at temperatures approaching 50°C.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide
IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

Page 6 of 7

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average



SDS Date: 03 Oct 2024

Revision No: 1.2

PRODUCT NAME FORCH RTV SILICONE MOTOR / HOUSING SEALING COMPOUND 200 ML

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711

Fax: +61 8 9322 1794 Email: info@rmtglobal.com Web: www.rmtglobal.com

[End of SDS]



SDS Date: 03 Oct 2024

Revision No: 1.2